

CORSO LED v2

Stropní LED svítidlo



[V]
220-240
AC

[Hz]
50

[°]
120

[h]
≥20000

[h]
25000

ellipso
≤ 6x MacAdam

Ra
80

Hg

SMD

IP
44

[°C]
-20÷35

0,5m



CORSO LED V2 12-NW

		 [W]	 [lm]	 Tc [K]		 SENSOR
CORSO LED V2 12-NW	31220	12	900	4000	bílá	
CORSO LED V2 18-NW	31221	18	1200	4000	bílá	
CORSO LED V2 24-NW	31222	24	1700	4000	bílá	
CORSO LED V2 12-NW-SE	31223	12	900	4000	bílá	mikrovlnný
CORSO LED V2 18-NW-SE	31224	18	1200	4000	bílá	mikrovlnný
CORSO LED V2 24-NW-SE	31225	24	1700	4000	bílá	mikrovlnný

CORSO LED v2

Stropní LED svítidlo



CORSO LED V2 12-NW



CORSO LED V2 18-NW



CORSO LED V2 24-NW




CORSO LED V2 12-NW-SE




CORSO LED V2 18-NW-SE




CORSO LED V2 24-NW-SE




CORSO LED V2 12-NW



CORSO LED V2 18-NW




CORSO LED V2 24-NW




CORSO LED V2 12-NW-SE

CORSO LED v2

Stropní LED svítidlo



CORSO LED V2 18-NW-SE



CORSO LED V2 24-NW-SE